

MAGNETIC LOCKS AND BRACKETS

| MAGNETIC LOCKS | Code | Description |
|------------------|-------------|--|
| | 12V-300-F/S | SLIMLINE FRONT MOUNT MAGNETIC LOCK 12V 300 KG WITH WIRE EXITING THE BOX ON THE SIDE LOCK: LENGTH - 219mm / WIDTH - 49mm / HEIGHT - 29mm. STRIKER PLATE: LENGTH - 219mm / WIDTH - 49mm / HEIGHT - 12mm. CURRENT: 480 ma (MAX) AT 12v DC DOOR SENSING CONTACT RATED AT 12v DC 1 amp |
| | 12V-300-F/B | SLIMLINE FRONT MOUNT MAGNETIC LOCK 12V 300 KG WITH WIRE EXITING THE BOX AT THE BACK. LOCK: LENGTH - 219mm / WIDTH - 49mm / HEIGHT - 29mm. STRIKER PLATE: LENGTH - 219mm / WIDTH - 49mm / HEIGHT - 12mm. CURRENT: 480 ma (MAX) AT 12v DC DOOR SENSING CONTACT RATED AT 12v DC 1 amp |
| | 12V-300-S | SLIMLINE SIDE MOUNT MAGNETIC LOCK 12V 300 KG. LOCK: LENGTH - 219mm / WIDTH - 49mm / HEIGHT - 29mm. STRIKER PLATE: LENGTH - 219mm / WIDTH - 49mm / HEIGHT - 12mm. CURRENT: 480 ma (MAX) AT 12v DC DOOR SENSING CONTACT RATED AT 12v DC 1 amp |
| ALL OF THE OWNER | 12V-300-U | SLIMLINE UNIVERSAL MOUNT MAGNETIC LOCK 12V 300KG Note:THIS LOCK CAN BE EITHER MOUNTED AS SIDE OR FRONT. IT IS IMPORTANT TO SELECT THE APPROPRIATE BRACKET FOR MOUNTING, OR ALTERNATIVELY TAKE BOTH TO SITE. REMEMBER, IF THE UNIVERSAL LOCK IS TO BE FRONT MOUNTED, A "Z" BRACKET WILL BE REQUIRED LOCK: LENGTH - 219mm / WIDTH - 49mm / HEIGHT - 29mm. STRIKER PLATE: LENGTH - 219mm / WIDTH - 49mm / HEIGHT - 12mm. CURRENT: 480 ma (MAX) AT 12v DC DOOR SENSING CONTACT RATED AT 12v DC 1 amp |
| | 12V-500-F/S | HEAVY DUTY FRONT MOUNT MAGNETIC LOCK 12V 500KG WITH WIRE EXITING THE BOX ON THE SIDE LOCK: LENGTH - 219mm / WIDTH - 75mm / HEIGHT 45mm STRIKER PLATE: LENGTH - 219mm / WIDTH - 75mm / HEIGHT - 10mm CURRENT: 260 ma AT 12v DC DOOR SENSING CONTACT RATED AT 12v DC 1 amp |
| | 12V-500-F/B | HEAVY DUTY FRONT MOUNT MAGNETIC LOCK 12V 500 KG WITH WIRE EXITING THE BOX AT THE BACK. LOCK: LENGTH - 219mm / WIDTH - 75mm / HEIGHT 45mm STRIKER PLATE: LENGTH - 219mm / WIDTH - 75mm / HEIGHT - 10mm CURRENT: 260 ma AT 12v DC DOOR SENSING CONTACT RATED AT 12v DC 1 amp |

| MAGNETIC L | OCKS |
|------------|------|
| | |

Code

Description

| | 12V-500-S | HEAVY DUTY SIDE MOUNT MAGNETIC LOCK 12V. 500 KG. LOCK: LENGTH - 219mm / WIDTH - 75mm / HEIGHT 45mm STRIKER PLATE: LENGTH - 219mm / WIDTH - 75mm / HEIGHT - 10mm CURRENT: 260 ma AT 12v DC DOOR SENSING CONTACT RATED AT 12v DC 1 amp |
|--|---------------------|--|
| | 24V-40-S | FIRE MAGNETIC LOCK SIDE MOUNT 24 V. USED FOR HOLDING OPEN FIRE DOORS. COMPLETE WITH OPERATING INDICATION (RED LED) AND A RELEASE PUSH BUTTON. LOCK: LENGTH - 110mm / WIDTH - 48mm / HEIGHT - 30mm STRIKER PLATE: LENGTH - 110mm / WIDTH - 48mm / HEIGHT - 10mm CURRENT: 92 ma AT 24v DC DOOR SENSING CONTACT RATED AT 12v DC 1 amp |
| A REAL OF AN | 12V-200-M- SS37 | MORTICE MAGNETIC LOCK 12V 200 KG HOLDING POWER THE LOCK COMES WITH BRACKETS ON THE SIDE TO ALLOW A FLUSH INSTALLATION IN AN ALUMINIUM TRANSAM DOOR. SENSING CONTACT RATED AT 12v DC 1amp LOCK: LENGTH – 200mm / WIDTH – 37mm / HEIGHT – 28mm. STRIKER PLATE: LENGTH – 170mm / WIDTH – 37mm / HEIGHT – 11mm. CURRENT: 450ma AT 12v DC |
| BIR WAY SO S | 12V-300-M- SS37 | MORTICE MAGNETIC LOCK 12V 300 KG HOLDING POWER THE LOCK COMES WITH BRACKETS ON THE SIDE TO ALLOW A FLUSH INSTALLATION IN AN ALUMINIUM TRANSAM DOOR. SENSING CONTACT RATED AT 12v DC 1amp LOCK: LENGTH – 270mm / WIDTH – 37mm / HEIGHT – 38mm. STRIKER PLATE: LENGTH – 240mm / WIDTH – 37mm / HEIGHT – 11mm. CURRENT: 460ma AT 12v DC |
| N S S S S S S S S S S S S S S S S S S S | 12V-300-M- SHEAR | SHEAR MAGNETIC LOCK 12V IN EXCESS OF 300 KG HOLDING POWER THE LOCK COMES WITH BRACKETS ON THE SIDE TO ALLOW A FLUSH INSTALLATION IN AN ALUMINIUM TRANSAM DOOR. SENSING CONTACT RATED AT 12v DC 1amp LOCK: LENGTH – 200mm / WIDTH – 32mm / HEIGHT – 28mm. STRIKER PLATE ASSEMBLY: LENGTH – 220mm / WIDTH – 37mm / HEIGHT – 30mm. CURRENT: 450ma AT 12v DC |
| | 12V-140-S-BEL | BELL MAGNETIC LOCK 12V 140 KG HOLDING POWER THE LOCK COMES WITH A QUICK MOUNT BRACKET LOCK: LENGTH – 170mm / WIDTH – 33mm / HEIGHT – 22mm. STRIKER PLATE: LENGTH – 130mm / WIDTH – 33mm / HEIGHT – 11mm. CURRENT: 350ma AT 12v DC THESE PRICES ARE SUBJECT TO THE CURRENT EXCHANGE RATE AND ARE SUBJECT TO CHANGE WITHOUT NOTICE |
| | 12V-270-S-BEL | BELL MAGNETIC LOCK 12V 270 KG HOLDING POWER THE LOCK COMES WITH A QUICK MOUNT BRACKET LOCK: LENGTH – 250mm / WIDTH – 42mm / HEIGHT – 26,5mm. STRIKER PLATE: LENGTH – 180mm / WIDTH – 38mm / HEIGHT – 11mm. CURRENT: 450ma AT 12v DC THESE PRICES ARE SUBJECT TO THE CURRENT EXCHANGE RATE AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. |

| BRACKETS | Code | Description |
|------------------------|------------------|---|
| | QMFMB-300 | QUICK MOUNT FRONT MOUNT BRACKET FOR 300 KG FRONT MOUNT MAGNETIC LOCK NOTE THAT THIS BRACKET MAY ALSO BE USED ON THE SLIMLINE UNIVERSAL MAGNETIC LOCK WHEN USED IN THE FRONT MOUNT POSITION. DIMENSIONS: 219 x 48 x 6mm FLAT BAR |
| THE CONTRACT OF STREET | QMFMB-300 F/B | QUICK MOUNT FRONT MOUNT BRACKET FOR 300 KG FRONT MOUNT MAGNETIC LOCK NOTE THAT THIS BRACKET IS SPECIFICALLY DRILLED OPEN TO FIT A 12V-300- F/B MAGNETIC LOCK WHEN USED IN THE FRONT MOUNT POSITION, WITH THE CONNECTING CABLE PENETRATING AT THE BACK OF THE LOCK DIMENSIONS: 219 x 48 x 6mm FLAT BAR |
| | QMFMB-500 | QUICK MOUNT FRONT MOUNT BRACKET FOR 500 KG FRONT MOUNT MAGNETIC LOCK DIMENSIONS: 218 x 75 x 7,6mm FLAT BAR |
| CO SOS: | QB-40 | QUICK MOUNT SIDE MOUNT BRACKET FOR 40 KG FIRE MAGNETIC LOCK DIMENSIONS: 110 x 25,4 x 9,8mm FLAT BAR |
| PHURINITY STORES | QB-300 | QUICK MOUNT SIDE MOUNT BRACKET FOR 300 KG SIDE MOUNT MAGNETIC LOCK NOTE THAT THIS BRACKET MAY ALSO BE USED ON THE SLIMLINE UNIVERSAL MAGNETIC LOCK FOR EITHER SIDE OR FRONT MOUNT APPLICATIONS. DIMENSIONS: 219 x 25,4 x 9,8mm FLAT BAR |
| | QB-500 | QUICK MOUNT SIDE MOUNT BRACKET FOR 500 KG SIDE MOUNT MAGNETIC LOCK DIMENSIONS: 219 x 45 x 9,8mm FLAT BAR |
| HIT CON | EQMB-300 | EXTENDED QUICK MOUNT BRACKET TO MOUNT A SLIMLINE SIDE MOUNT MAGNETIC LOCK. NOTE THAT THIS BRACKET MAY ALSO BE USED TO MOUNT A SLIMLINE UNIVERSAL 300 KG MAGNETIC LOCK. THIS BRACKET IS A REAL TIME SAVER AND ENHANCES THE ESTETICAL LOOK OF THE INSTALLATION IT IS A GREAT ALTERNATIVE TO THE OLD ANGLE AND L BRACKET. DIMENSIONS: 219 x 38,7 x 6mm FLAT BAR |

Code

Description

| BRACKETS | Code | Description |
|----------|-----------|--|
| | DWFMB-300 | DRY WALL FRONT MOUNT BRACKET TO MOUNT A SLIMLINE FRONT MOUNT MAGNETIC LOCK ON A DOOR INSTALLED IN A DRYWALL (PARTITION WALL). DIMENSIONS: 219 x 48 x 6mm FLAT BAR |
| | ZB-300 | "Z" BRACKET FOR A 300 KG FRONT MOUNT MAGNETIC LOCK NOTE THAT THIS BRACKET MAY ALSO BE USED WHERE A SLIMLINE UNIVERSAL 300 KG IS USED IN A FRONT MOUNT POSITION. DIMENSIONS: TWO PIECES OF 219 x 50 x 50mm ANGLE JOINED TOGETHER WITH AN ADJUSTABLE MECHANISM |
| | ZB-500 | "2" BRACKET FOR A 500 KG FRONT MOUNT MAGNETIC LOCK DIMENSIONS: TWO PIECES OF 219 x 76,5 x 60mm ANGLE JOINED TOGETHER WITH AN ADJUSTABLE MECHANISM. |
| 2 2 | SB-300 | SPACER BRACKET FOR SLIMLINE SIDE MOUNT MAGNETIC LOCK 300 KG DIMENSIONS: 219 x 25,4 x 9,8mm FLAT BAR. |
| | AB-300 | ANGLE BRACKET FOR SLIMLINE SIDE MOUNT MAGNETIC LOCK 300 KG DIMENSIONS: 219 x 38 x 38mm ANGLE |
| | LB-300 | "L" BRACKET FOR SLIMLINE SIDE MOUNT MAGNETIC LOCK 300 KG DIMENSIONS: 219 x 25,4 x 38mm ANGLE |
| | LZB-140 | "L Z " BRACKET FOR BELL 140 SIDE MOUNT MAGNETIC LOCK THESE PRICES ARE SUBJECT TO THE CURRENT EXCHANGE RATE AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. |
| B. C | LZB-270 | "L Z " BRACKET FOR BELL 270 SIDE MOUNT MAGNETIC LOCK THESE PRICES ARE SUBJECT TO THE CURRENT EXCHANGE RATE AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. |