



**Dimensions** Unit : mm (ft-in)

	ViO17
A	2200 (7'03")
B	2310 (7'7")
C	1850 (6'1")
D	3710 (12'2")
E	3450 (11'4")
F	1525 (5'0")
G	3690 (12'1")
H	2630 (8'8")
I	1535 (5'0")
J	2300 (7'7")
K	260 (10")
L	950 (3'1") 1280 (4'2")
M	230 (9")
N	175 (7")
O	125 (5")
P	640 (2'1")
Q	400 (1'4")
R	85 (3")
S	R640 (2'1")

**Specifications**

Model		ViO17	
Type		Canopy	
Operating weight	Rubber track	kg (lbs)	1740 (3836)
	Steel track	kg (lbs)	1800 (3969)
Engine	Type	-	Water-cooled 3 cycle diesel
	Model	-	3TNV70-XBV
	Output	kW (hp) / rpm	10.1 (13.5) / 2200
Performance	Bucket capacity, standard (ISO heaped)	cu.m (cu.ft)	0.05 (1.77)
	Max digging force, bucket / arm	kN (lbf)	15.2 (3417) / 8.5 (1918)
	Traveling speed, high / low	km/h (MPH)	4.3 / 2.1 (2.7 / 1.3)
	Swing speed	RPM	9.5
	Boom swing angle, (L / R)	degrees	42 / 65
Ground contact pressure	Rubber track	kPa (PSI)	28.6 (4.1)
	Steel track	kPa (PSI)	29.6 (4.3)
Hydraulic system	Pump capacity	L / min (GPM)	17.6 + 17.6 + 13.2 + 11.2 (4.6 + 4.6 + 3.5 + 2.6)
	Main relief set pressure	MPa (PSI)	20.6 (2987)
Undercarriage	Track type	-	Rubber
Blade dimensions	Width x height	mm (ft-in)	1280 / 950 x 235 (4'2" / 3'1" x 9")
Fuel tank capacity		L (Gals)	20 (5.3)

**Standard Equipment**

- Blade
- Boom swing function
- Cylinder cover (boom, arm, bucket, blade)
- Rubber or Steel tracks
- ROPS / FOPS canopy
- Joystick pilot controls
- Arm rests
- Sliding seat
- Seat belt
- Travel levers and pedals
- Floor mats
- Built-in type boom light
- Variable track

Please note that the standard equipment may vary from this list. Consult your Yanmar dealer for confirmation

**Hydraulic P.T.O**

Model		ViO17	
Specification	Output	L / min (GPM)	
		MPa (PSI)	
Combined flow, double actions			2200RPM
			1250RPM
		16.7 (2417)	30.8 (8.1) / 17.5 (4.6)